

UT-300R A (CPE)

MULTI-MODE ADSL MODEM

DELIVERS HIGH-SPEED DATA OVER PHONE LINES, PROVIDING ROUTING, GATEWAY AND FIREWALL CAPABILITIES



KEY FEATURES

- Designed for residential, small LAN and SOHO applications
- High speed asymmetrical data transmission on a single twisted pair
 - Full-rate operation up to 8Mbps/12Mbps downstream and 1Mbps upstream
 - G.lite operation up to 1.5Mbps down stream and 512Kbps upstream
- Built-in firewall capabilities include stateful packet inspection, Denial-of-Service (DoS), firewall trigger and URL-based content filtering
- Additional security via VPN IPSec pass through, L2TP client/server and L2TP/PPTP pass through, and ID password authentication
- Supports IP Multicast, IGMP v1/v2, TFTP, DHCP, Telnet, HTTP and FTP
- Supports PPPoE (RFC 2516), PPPoA (RFC 2364), Classical IP over ATM (RFC 2225/RFC 1577), and RFC 2684 (RFC 1483) protocols
- Configuration and network management via Telnet and Web browser
- DHCP server support for LAN IP address management
- Remote management via SNMP v1 and MIB II (RFC 1213)


INTERFACES

Customer Side

- One RJ45 connector (10/100BaseT Ethernet, IEEE 802.3)

Network Side

- One RJ11 connector
- Line impedance: 100 W
- Connection loop: Single pair (two-wire)
- Interoperability complies with TR-48



SPECIFICATIONS

Software

ATM

- ATM Cell over ADSL, AAL5
- UBR/GFR, CBR, VBR-rt and VBR-nrt
- VPI range (0-4095) and VCI range (1-65535)
- Supports up to 8 PVCs

Bridging

- Transparent bridging (IEEE 802.1D)
- RFC 2684 (RFC 1483) bridged
- Spanning Tree Protocol (IEEE 802.1D)

Routing

- RIP v1/v2 and static routing
- NAT/PAT – RFC 1631 (basic firewall support)
- Supports Point-to-Point Protocol (PPP)
- PAP or CHAP for user authentication
- RFC 2684 (RFC 1483) routed
- DNS relay

Hardware

Power

- AC adapter: 11 VDC, 700 mA (120 VAC/60 Hz or 230 VAC/50 Hz input)
- Power consumption: < 10.0 watts

Dimensions

- W x D x H: 140 x 135 x 26 mm

Environmental

- Operating: 0~45°C, 5~95% humidity
- Storage: -20~85°C, 5~95% humidity

Certifications

- CE, FCC Part 15 Class B, UL

Please note the information contained herein is for informational purposes only. Technical claims listed depend on a series of technical assumptions. Your experience with these products may differ if you operate the products in an environment, which is different from the technical assumptions. UTStarcom reserves the right to modify these specifications without prior notice. UTStarcom makes no warranties, express or implied, on the information contained in this document.

UTStarcom, Inc. USA

1275 Harbor Bay Parkway
 Alameda, CA 94502, USA
 Tel: 510-864-8800
 Fax: 510-864-8802

www.utstar.com

About UTStarcom, Inc.

UTStarcom is a global leader in IP-based, end-to-end networking solutions and international service and support. The company sells its broadband, wireless, and handset solutions to operators in both emerging and established telecommunications markets around the world. UTStarcom enables its customers to rapidly deploy revenue-generating access services using their existing infrastructure, while providing a migration path to cost-efficient, end-to-end IP networks. Founded in 1991 and headquartered in Alameda, California, the company has research and design operations in the United States, China, Korea and India. UTStarcom is a FORTUNE 1000 company. For more information about UTStarcom, visit the company's Web site at www.utstar.com

Copyright © 2005 UTStarcom, Inc. All Rights Reserved. UTStarcom is a registered trademark and the UTStarcom logo and A World of Better Communication are trademarks of UTStarcom, Inc. and its subsidiaries.